



ATC5050

Product Features:

- 9.1-oz, 50/50 cotton/polyester
- Compacted yarns to minimize shrinkage
- Comfort Dry fabric blend offers breathability and wicks moisture away from skin

Adult sizes: S-6XL

Icons/Fabric Features:



Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print pantone reference



ATC5050 - ATC™ Everyday Cotton Blend Tee

GARMENT MEASUREMENTS

Size	S	M	L	XL	2XL	3XL	4XL	5XL	6XL
Chest - <i>Half Measure</i>	18"	20"	22"	24"	26"	28"	30"	32"	34"
Chest - <i>Full Measure</i>	36"	40"	44"	48"	52"	56"	60"	64"	68"
Body Length from HPS	28"	29"	30"	31"	32"	33"	34"	35"	36"
Sleeve Length-CB	16 3/4"	17 3/4"	18 3/4"	19 3/4"	20 3/4"	21 3/4"	22 3/4"	23 3/4"	24 3/4"

Finished measurements in inches. Refer to "How to Measure" guide for detailed information on measurement instructions.

ADULT General Sizing Guide

Size	S	M	L	XL	2XL	3XL	4XL	5XL	6XL
Chest	34"-36"	38"-40"	42"-44"	46"-48"	50"-52"	54"-55"	56"-57"	58"-61"	61"-64"
Waist	29"-32"	32"-35"	35"-38"	38"-41"	41"-44"	44"-47"	47"-50"	50"-53"	53"-56"
Sleeve Length-CB	32"-33 1/2"	34"-35"	35"-36"	36"-37"	37"-38"	38"-39"	38 1/2"-39"	39"-39 1/2"	39 1/2"-40"



**EVERYDAY
COLLECTION**

DECORATING INSTRUCTIONS FOR 50/50 COTTON/POLY SAFETY COLOURS

Due to the nature of fluorescent dyes in Safety colours, special care must be taken throughout the decoration process. Here are some tips to effectively decorate printed fabrics:

- Garment temperature must not exceed 320°F or 160°C. Exceeding this temperature may cause discoloration
- Dryer temperature and belt speeds must be changed accordingly for fluorescent colours. Check the dryer for proper clearance. When placing garments on the belt, carefully lay them as flat as possible to avoid high spots that may touch the inside of the dryer or come closer to heat elements. Garments touching a hot piece of the dryer may result in discoloration.
- If flashing these garments, do not exceed 2-3 seconds and care should be taken to not have the flash cure unit too close to the garment

Screen Printing:

- Dwell times in the dryer need to be limited to no more than 90 seconds
- Do not exceed recommended dryer temperature
- Check with your ink supplier for more information.

Heat Transfer Tips:

- Direct heat contact can cause discoloration. Use cover sheet/flexible application sheet to shield upper platen from garment
- Do not exceed recommended temperature
- Check with your heat transfer supplier for more information

A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on performance fabrics.